



certifix
YOUR FIXING SPECIALIST

Certifix CFRP-7K-P

Self drilling, sandwich screw



APPLICATIONS

Fixing sandwich profiles to steel

PRODUCT FEATURES

- Suitable for fixing to standard coupling purlins
- 7mm thread-free section behind the drill tip prevents forced feed, which can be caused by structural tolerances

TECNICAL DATA

- Material: Bimetal (A2 stainless steel/steel)
- Drilling capacity [mm]: 1.5 - 5.25mm
- Drive: AF 8
- Processing speed [rpm]: 1.400
- Head diameter [mm]: 10.7mm

DRILLING CAPACITY

- Component 1 [mm]: Steel 0.4 - 1.0mm
- Component 2 [mm]: Steel 1.5 - 4.0mm





Designation	Dia. [mm]	Length [mm]	Thread length [mm]	Steel clamping area [mm]	Unit	EAN
Sealing washer E16						
CFRP-7K-P	5.5	76	37.5	36 - 47	100	4005674 17007 9
		85	42.5	40 - 56	100	4005674 17008 6
		99	47.5	49 - 70	100	4005674 17009 3
		126	61.5	62 - 97	100	4005674 17011 6
		142	71.5	68 - 113	100	4005674 17013 0
		162	71.5	88 - 133	100	4005674 17014 7
		185	92.5	90 - 156	100	4005674 17016 1
		210	92.5	115 - 181	100	4005674 17017 8
		235	92.5	140 - 206	50	4005674 17018 5
Sealing washer E19						
CFRP-7K-P	5.5	76	37.5	36 - 47	100	4005674 17019 2
		85	42.5	40 - 56	100	4005674 17020 8
		99	47.5	49 - 70	100	4005674 17021 5
		126	61.5	62 - 97	100	4005674 17022 2
		142	71.5	68 - 113	100	4005674 13793 5
		162	71.5	88 - 133	100	4005674 17023 9
		185	92.5	90 - 156	100	4005674 17025 3
		210	92.5	115 - 181	100	4005674 17026 0
		235	92.5	140 - 206	50	4005674 17027 7
Sealing washer E22						
CFRP-7K-P	5.5	76	37.5	36 - 47	100	4005674 17028 4
		85	42.5	40 - 56	100	4005674 17029 1
		99	47.5	49 - 70	100	4005674 17030 7
		126	61.5	62 - 97	100	4005674 17031 4
		142	71.5	68 - 113	100	4005674 17032 1
		162	71.5	88 - 133	100	4005674 17033 8
		185	92.5	90 - 156	100	4005674 17034 5
		210	92.5	115 - 181	100	4005674 17036 9
		235	92.5	140 - 206	50	4005674 17037 6



Z-14.4-407, annex 2.47/2.56

